



Gasket Tape Series 500

Product Supplement

Now Available: Cold Temperature Adhesive (CTA) Option

SOMETIMES YOU'D RATHER NOT BE OUTSIDE. BUT THE FLANGES ARE.

Gore's form-in-place gasket products, with their convenient customization, provide an excellent solution for large flanges. But often those flanges are located outside and are exposed to cold weather. Low temperatures may significantly decrease the effectiveness of standard adhesives, making it difficult to install form-in-place gasket products.

MADE FOR EXTREME CONDITIONS

Gore's cold temperature adhesive (CTA) is specially formulated to stick to flanges in extreme cold temperatures—down to 0°F (-18°C).

PRODUCT SIZES

The cold temperature adhesive option is available* on these sizes of GORE® Gasket Tape Series 500:

Thickness	Width	Length
3 mm (1/8 in)	15 mm (3/4 in)	25 ft
		50 ft
	25 mm (1 in)	25 ft
		50 ft
6 mm (1/4 in)	15 mm (3/4 in)	25 ft
		50 ft
	25 mm (1 in)	25 ft
		50 ft

**Due to the seasonal requirement for cold temperature adhesive, availability of the CTA option may be limited or suspended during the warm-season months. Gore's return/restocking policy is not available for CTA products.*

TYPICAL APPLICATIONS


GORE® Gasket Tape Series 500 with cold temperature adhesive can be used in any application for which GORE® Gasket Tape Series 500 with the standard adhesive is used. This includes large and/or non-standard steel equipment flanges, vessel and tank process flanges and manways, large diameter piping, heat exchangers and baffles. It is the same high-performing 100% ePTFE product.

FOR INDUSTRIAL USE ONLY. Not for use in food, drug, cosmetic or medical device manufacturing, processing, or packaging operations.

All technical information and advice given here is based on Gore's previous experiences and/or test results. Gore gives this information to the best of its knowledge, but assumes no legal responsibility. Customers are asked to check the suitability and usability in the specific application, since the performance of the product can only be judged when all necessary operating data are available. The above information is subject to change and is not to be used for specification purposes.

Gore's terms and conditions of sale apply to the sale of the products by Gore. GORE and designs are trademarks of W. L. Gore & Associates. ©2015 W. L. Gore & Associates, Inc.

SELECTING THE RIGHT GORE ADHESIVE



Adhesive range of use may vary based on installation specific conditions including but not limited to surface conditions such as temperature, roughness, and cleanliness including moisture; as well as the specific combination of the Gore Sealant product used and the shape / bend radii of the installation.

LOOK FOR THE BLUE STICKER



To identify Gore Sealants products with cold temperature adhesive, look for the blue sticker on the box and spool, and the blue adhesive on the product.

Note that spools with the CTA option are wound with the adhesive facing inside. This will not affect the installation procedure or gasket tape performance.

Supplied By:

W. L. Gore & Associates Inc. (USA)
Toll Free: 800.455.2791
Tel: +1 410.506.1821
Email: sealants@wlgore.com
Website: www.gore.com/sealants



SEAL-557-TEC-US-DECT 5